

HIRE - MAX PETROL RANGE

FITTED WITH MARKON NAC ALTERNATORS



2700HM

2.7kVA • 2.2KW • HONDA GX160



3400HM

3.4kVA • 2.7KW • HONDA GX200



5000HM

5.0kVA • 4.0KW • HONDA GX270



6000HM

6.0kVA • 4.8KW • HONDA GX340



6500HM

6.5kVA • 5.2KW • HONDA GX390

Standard Features

- Honda four stroke engines with oil alert
- Noise compliant using the latest low noise engine specification
- Dual voltage output c/w overload protection
- Fully welded industrial carry frames for maximum strength
- Brushless maintenance free Markon alternators with exceptional component design quality
- Rubber bushed control boxes for longevity of electrical components

STANDARD SPECIFICATIONS

ADDITIONAL OPTIONS

Model	AVR	Electric Start	Electrofusion TIN 12 Versions Available	Gas Conversion	Long Range Steel Fuel Tank	Single Voltage (115 or 230v)	Trolley Kit
2700HM		✓		✓ 030-001	✓	✓	✓ TK1100
3400HM				✓ 030-001	✓	✓	✓ TK1100
5000HM	✓	✓	✓	✓ 030-002	✓	✓	✓ TK1101
6000HM	✓		✓	✓ 030-003	✓	✓	✓ TK1101
6500HM	✓	✓	✓	✓ 030-003	✓	✓	✓ TK1101

Model	HP/Cyl	Start	Sockets				Fuel Tank (LT)	Run Time @75% Load	Noise		Dimensions			
			115V		230V				7M	dB Lwa	Wt	L	W	H
			16A	32A	16A	32A								
2700HM	5.5/1	RC	1	-	1	-	3.6	3.6	70	95	36	610	420	410
3400HM	6.5/1	RC	1	-	1	-	3.6	3.0	71	96	41	610	420	410
5000HM	9.0/1	RC	2	1	2	-	6.0	3.5	71	96	59	690	480	540
6000HM	11.0/1	RC	2	1	2	-	6.5	3.0	72	97	68	690	480	540
6500HM	13.0/1	RC	2	1	2	-	6.5	2.6	72	97	71	690	480	540